

SB 5-6 / SB 5-6

6V 5.0Ah

SB 5-6 / SB 5-6 is a general purpose battery with 6~9 years in standby service or more than 400 cycles at 50% depth of discharge in cycle service.


☆ SPECIFICATION

● NOMINAL VOLTAGE	: 6.0 V
● NOMINAL CAPACITY(20 hr)	: 5.0 Ah
● DIMENSIONS	
TOTAL HEIGHT	: 106 mm (4.17 inches)
CONTAINER HEIGHT	: 101mm (3.98inches)
LENGTH	: 70 mm (2.76inches)
WIDTH	: 48mm (1.89 inches)
● WEIGHT	: APPROX 0.70 Kg (1.54 lbs)
● CONTAINER MATERIAL	: UL94HB ABS
● INTERNAL RESISTANCE(25°C , 77 °F)	: ~25m
● DISCHARGE CAPACITY UNDER DIFFERENT TEMPERATURES	
40°C	: ~102%
25°C	: ~100%
0 °C	: ~85%


☆ CHARACTERISTICS

● CAPACITY 25 °C / 77 °F	
20 hr @ 0.25 A	: 5.00 Ah
5 hr @ .0.80 A	: 4.00 Ah
1 hr @ 3.00 A	: 3.00 Ah
1 C @ 5.00 A	: 2.50 Ah
● CHARGING VOLTAGE (25°C , 77 °F)	
STANDBY USE	: 6.7 V 6.90 V
CYCLE USE	: 7.2 V 7.50 V
● MAX DISCHARGE CURRENT	: 37.5 A (5 sec)
● MAX CHARGING CURRENT	: 1.50 A
● SELF-DISCHARGE RESIDUAL CAPACITY(25°C , 77 °F)	
AFTER 3 MONTHS	: ~90%
AFTER 6 MONTHS	: ~82%
AFTER 12 MONTHS	: ~64%


☆ Discharge Current vs Time



☆ Discharge Characteristics @25 °C (77 °C)



☆ Dimensions



☆ Terminal

