

# SBL 40-12i

## 12V 40Ah

SBL 40-12i is a high performance battery with 10-12 years lifetime in standby service or more than 400 cycles at 50% depth of discharge in cycle service.


### ☆ SPECIFICATION

● NOMINAL VOLTAGE	: 12V
● NOMINAL CAPACITY(20 hr)	: 40Ah
● DIMENSIONS	
TOTAL HEIGHT	: 170 mm ( 6.69 inches )
CONTAINER HEIGHT	: 170 mm ( 6.69 inches )
LENGTH	: 197 mm ( 7.76 inches )
WIDTH	: 165 mm (6.50 inches )
● WEIGHT	: APPROX 13.5Kg ( 29.8 lbs )
● CONTAINER MATERIAL	: UL94HB ABS
	: UL94V-0 ABS
● INTERNAL RESISTANCE( 25°C , 77 °F )	: ~9.5m
● DISCHARGE CAPACITY UNDER DIFFERENT TEMPERATURES	
40°C	: ~102%
25°C	: ~100%
0 °C	: ~85%


### ☆ CHARACTERISTICS

● CAPACITY 25°C/77°F	
20hr @ 2A	: 40 Ah
5hr @ 6.8A	: 34Ah
1hr @ 24.9A	: 24.9Ah
1C @ 40A	: 20Ah
● CAPACITY 25°C/77°F	
STANDBY USE	:13.65V±0.15V
CYCLE USE	:14.7V ± 0.3V
● MAX DISCHARGE CURRENT	:400A(5sec)
● MAX CHARGING CURRENT	:12A
● SELF-DISCHARGE RESIDUAL CAPACITY	
AFTER 3 MONTHS	:~90%
AFTER 6 MONTHS	:~82%
AFTER 12 MONTHS	:~70%


### ☆ Discharge Current vs Time



### ☆ Discharge Characteristics @25 °C (77 °F)



### ☆ Dimensions



### ☆ Terminal

