



SBLFT 75-12i

12V 75Ah

Front Access Terminal

SBLFT 75-12i is a High Performance battery with 12 years in standby service or more than 350 cycles at 50% depth of discharge in cycle service.


☆ SPECIFICATION

● NOMINAL VOLTAGE	: 12V
● NOMINAL CAPACITY(20 hr)	: 75Ah
● DIMENSIONS	
TOTAL HEIGHT	: 188 mm (7.40 inches)
CONTAINER HEIGHT	: 188 mm (7.40 inches)
LENGTH	: 563 mm (22.17 inches)
WIDTH	: 114 mm (4.49 inches)
● WEIGHT	: APPROX 24Kg (52.9 lbs)
● CONTAINER MATERIAL	: UL94HB ABS
	: UL94V-0 ABS
● INTERNAL RESISTANCE(25°C , 77 °F)	: ~5.7m
● DISCHARGE CAPACITY UNDER DIFFERENT TEMPERATURES	
40°C	: ~102%
25°C	: ~100%
0 °C	: ~85%


☆ CHARACTERISTICS

● CAPACITY 25°C/77°F	
20hr @ 3.75 A	:75 Ah
5hr @ 13,0 A	:65 Ah
1hr @ 53,0 A	:53 Ah
1C @ 75,0 A	:37.5 Ah
● CAPACITY 25°C/77°F	
STANDBY USE	:13.65V±0.15V
CYCLE USE	:14.7V ± 0.3V
● MAX DISCHARGE CURRENT	:700A (5sec)
● MAX CHARGING CURRENT	:22.5A
● SELF-DISCHARGE RESIDUAL CAPACITY	
AFTER 3 MONTHS	:~90%
AFTER 6 MONTHS	:~82%
AFTER 12 MONTHS	:~70%


☆ Discharge Current vs Time



☆ Discharge Characteristics @25 °C (77 °F)



☆ Dimensions



☆ Terminal

