






## VRLA Battery **SPB 6-100**

### Specifications

<b>Nominal Voltage</b>	<b>6 V</b>				
<b>Rated Capacity (25 °C)</b>	<b>20hr Rate (1,80V/cell)</b>	<b>10hr Rate (1,80V/cell)</b>	<b>5hr Rate (1,70V/cell)</b>	<b>1hr Rate (1,60V/cell)</b>	
	107,4 Ah	100 Ah	92 Ah	72,4 Ah	
<b>Dimensions (mm) &amp; Weight (kg)</b>	<b>Length</b>	<b>Width</b>	<b>Height</b>	<b>Overall Height</b>	<b>Weight</b>
	193mm	168mm	204mm	208mm	16 kg
<b>Number / Type of Terminals</b>	<b>2 / M6</b>				

### Technical Characteristics

<b>Design Life at 20°C</b>	10-12 years	
<b>Eurobat Classification</b>	High Performance	
<b>Internal Resistance (Fully charged - 25°C)</b>	4 mΩ	
<b>Short-circuit current</b>	3200 A	
<b>Max Charging Current</b>	27 A	
<b>Min safe end Discharge Voltage</b>	1,60 V/cell	
<b>Self discharge per month at 20°C</b>	3%	
<b>Recommended Charging Voltage at 20°C</b>	Stand-by use (V/cell): 2,25 to 2,30	Cycle use (V/cell): 2,40 to 2,50
<b>Container Material</b>	ABS-UL94 HB	
<b>Electrolyte Type</b>	Sulfuric Acid	
<b>Type of plates / Alloy</b>	Flat plates / Lead-Calcium-Tin alloy	
<b>Type of Separator</b>	Absorbant Glass Mat	
<b>Valve Type / Operational Pressure</b>	Rubber / 1-3 psi (70-200 mbar)	
<b>Operating Temperature Range</b>	-20 to + 50°C	
<b>Storage time at 20°C</b>	9 months	



#### SUNLIGHT SYSTEMS S.A.

##### Headquarters

23rd km. N.R. Athens-Lamia  
145 65 Ag. Stefanos, Attica, Greece  
Tel.: +30 210 6242000  
Fax : +30 210 6216911

##### Manufacturing Plant

Neo Olvio  
67 200 Xanthi, Greece  
Tel.: +30 25410 48100  
Fax : +30 25410 95446

 **SUNLIGHT**  
creating energy  
[www.sunlight.gr](http://www.sunlight.gr)