



# VRLA Battery **SVTX 600**





## Specifications

**Nominal Voltage** 2 V

Rated Capacity (20 °C)	20hr Rate (1,80V/cell)	10hr Rate (1,80V/cell)	5hr Rate (1,70V/cell)	1hr Rate (1,60V/cell)			
	624 Ah	600 Ah	550 Ah	410 Ah			
Dimensions (mm) & Weight (kg)	Length	Width	Height	Overall Height	Weight		
	208 mm	270 mm	263 mm	272 mm	37.5 kg		
<b>Number / Type of Terminals</b>	<b>4 / M8</b>						

## Technical Characteristics

<b>Design Life at 20°C</b>	15 years
<b>Eurobat Classification</b>	Long Life
<b>Internal Resistance (Fully charged -25°C)</b>	0,15 m!
<b>Short-circuit current</b>	13700 A
<b>Max Charging Current</b>	180 A
<b>Min safe end Discharge Voltage</b>	1,60 V/cell
<b>Self discharge per month at 20°C</b>	3%
<b>Recommended Charging Voltage at 20°C</b>	Stand-by use (V/cell): 2,25 to 2,30 Cycle use (V/cell): 2,40 to 2,50
<b>Container Material</b>	ABS-UL94 HB
<b>Electrolyte Type</b>	Sulfuric Acid
<b>Type of plates / Alloy</b>	Flat plates / Lead-Calcium-Tin alloy
<b>Type of Separator</b>	Absorbant Glass Mat
<b>Valve Type / Operational Pressure</b>	Rubber / 1-3 psi (70-200 mbar)
<b>Operating Temperature Range</b>	-20 to 50°C
<b>Storage time at 20°C</b>	9 months



### SUNLIGHT SYSTEMS S.A.

#### Headquarters

23rd km. N.R. Athens-Lamia  
145 65 Ag. Stefanos, Attica, Greece  
Tel.: +30 210 6242000  
Fax: +30 210 6216911

#### Manufacturing Plant

Neo Olvio  
67 200 Xanthi, Greece  
Tel.: +30 25410 48100  
Fax: +30 25410 95446

 **SUNLIGHT**  
creating energy

www.sunlight.gr